

Robust A4 print solutions

These A4 printers set new benchmarks for speed and resilience. Their robust performance will enhance productivity and enable your business to meet critical deadlines.

Productive, non-stop performance

- 55 & 60 ppm print speeds
- Non-stop performance
- Up to 2600 sheets
- 1200 dpi image quality

Running at speeds of 55 and 60 pages a minute and with stacks of paper on line, Ricoh's P 800 and P 801 mono A4 printers will easily handle the most demanding high speed / high volume workgroup print requirements. And, what is more, with their long-life parts and high yield toner cartridges offering hassle-free and maintenance-free performance, they will go on and on and on.

Powerful Intel-based controller

- Fast job processing
- Uniform workflow
- Remote support
- Tap and go security



When productivity matters, the Ricoh P 800 and P 801 deliver. With their Intel processors effortlessly handling complex PCL and PostScript files, the first 1,200 dpi print is ready in 2.4 seconds. The advanced controller provides a uniform workflow across compatible Ricoh devices and can be used to run enterprise workflow solutions, such as Streamline NX. And, with Near Field Communication (NFC) a standard feature, secure authentication is as easy as tap and go.

Quietly effective and affordable

- Space-saving design
- BAM compliant
- Maintenance free
- Low running costs

These A4 printers can be positioned at the very heart of your operation. Compact, easy to use and utterly reliable, they produce high quality print communication, quickly and without fuss. The energy efficient printers comply with Blue Angel Mark (BAM) environmental standards, and with their long-life parts offering maintenance-free performance and high yield toner cartridges reducing running costs, they are arguably the most effective and affordable A4 mono printers available today.



RICOH P 800/P 801

MAIN SPECIFICATIONS

	P 800	P 801	
GENERAL			
Warm-up time	25.4 seconds 2.4 seconds		
First output speed: B/W Continuous output speed	2.4 secon 55 ppm	as 60 ppm	
Memory: standard	2 GB		
Memory: maximum	2 GB		
HDD: option Weight	320 GB 18 kg	3	
Dimensions: W x D x H	420 x 410 x 345 mm	443 x 410 x 365 mm	
Power source	220 - 240 V, 50	0/60 Hz	
PRINTER			
CPU	Intel® Atom Processor ApolloLake:1.3 GHz		
Printer language: standard	PCL5c PCL5e	PCL5c PCL5e	
	PCL6		
Printer language: option	PostScript 3 (emulation) Genuine Adobe ®PostScript®3™		
Time language. Spiloti	IPDS		
Drint resolution	PDF Direct from Adobe® 1,200 x 1,200 dpi		
Print resolution Network interface: standard	Ethemet 10 base-T/100 base-TX/1000 base-T		
	USB2.0		
Network interface: option	NFC Tag Bi-directional IEEE 1284/ECP		
темон полисо. Орион	Wireless LAN (IEEE 802.11ablg/n) USB Server for Second Network Interface		
Mobile printing capability	Apple AirPrint Mopria® Google Cloud Print NFC Ricoh Smart Device Print & Scan		
	Ricon Smart Device Ricon Smart Device		
Windows® environments	Windows® 7 Windows® 8.1 Windows® 10 Windows® Server 2008 Windows® Server 2012 Windows® Server 2012R2		
	Windows® Sen		
Mac OS environments UNIX environments	Macintosh OS X Native v10.11 or later UNIX Sun® Solaris10		
	HP-UX11.x11i v211i v3 SCO OpenServer5.0.76.0 RedHat® Linux Enterprise456		
SAP® environments	SAP® R/3®		
	SAP® S/4®		
PAPER HANDLING			
Recommended paper size	A4		
	A5 A6	A5 A6	
	B5 B6		
Paper input: standard	600 shee	ets	
Paper input: bypass		100 sheets	
Paper input: maximum	2,600 sheets		
Paper output: standard Paper output: maximum	500 shee 500 shee		
Paper weight	Trays:64 - 120 g/m²		
	Bypass:60 - 220 g/m² Duplex:64 - 120 g/m²		
Paper types	Plain paper Recycle paper Special paper		
	Color pap Letterhea		
	Cardstoo	ck	
	Preprinted p Bond pap		
	Coated pa	per	
	Envelop Gloss pap		
	Label pap	per	
	Thick pap OHP	er	

RICOH P 800/P 801

MAIN SPECIFICATIONS

Toner (ultra high yield) (P 801)

Consumable yield measuring method ISO/IEC 19752

		ECOLOGY
Less than 1,400 W		Power consumption: max.
749 W	716 W	Power consumption: operation
0.48 W		Power consumption: sleep
0.81 kWh	0.74 kWh	TEC* * It is a reference value based on the ENERGY STAR Ver.3.0 test method.
		OUTPUT TRAYS OPTIONS
		4x 500-sheet Paper tray
		CONSUMABLES
	10,000 prints	Starter toner
11,000 prints		
11,000 prints 500,000 sheets	,	Drum
		method. OUTPUT TRAYS OPTIONS

P 800



P 801

40,000 prints













