



## Installation Method



Ashlar

Herringbone

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see [www.interface.com/disclaimer](http://www.interface.com/disclaimer).

**Product** Brushed Lines **Colour** Graphite

**Product Specifications**

Product Number	A016
Product Construction	High Performance Luxury Vinyl Tile contains 39% Pre-Consumer Recycled Content
Finish	Ceramor - UV Stabilised Ceramic Bead Coating
Wear Layer Thickness	(EN ISO 24340) 0.55 mm
Total Thickness	(EN ISO 24346) 4.5 mm
Total Weight	6880 g/m <sup>2</sup>
Size	25cm x 1m
Tiles per Box	10 - 2.5m <sup>2</sup>
Backing	Sound Choice™ Acoustic Backing

**Performance Specifications**

Wear Classification	EN ISO 10874 33 Heavy Commercial / 42 General Light Industrial
CE Declaration Of Performance	<a href="#">DOP PBRG-AHCK3R</a>
UKCA Declaration of Performance	<a href="#">DOP PBRG-AHCK3R</a>
Castor Chair Rating	(ISO 4918 / EN425) Pass
Flammability	(EN ISO 9239-1) Euroclass Bfl-s1 (EN 13501-1)
Light Fastness	≥7 (ISO 105-B02)
Light Reflectance Value (LRV-L)	39.91
Light Reflectance Value (LRV-Y)	11.20
Dimensional Stability	(ISO 23999) ≤ 0.25 %
Curling	≤ 2 mm (ISO 23999)
Flexibility	(EN ISO 24344) Method A - Pass
Abrasion Resistance	(EN 660-2) Group T
Residual Indentation	≤0.2mm
Determination of Anti-Slip	(DIN 51130) R10
Pendulum Dry 4S	36+ (BS 7976-2) Low slip potential
Chemical Resistance	(EN ISO 26987) Very Good
Impact Sound Insulation ΔLw EN ISO 10140-3	16 dB

**Environmental Specifications**

Environmental Product Declaration	<a href="#">Download EPD</a>
Total Recycled Content	39 %
Indoor Air Quality	French A+ <a href="#">Indoor Air Comfort GOLD®</a> <a href="#">LVT Greenguard Gold</a> <a href="#">M1 Emission Certification - LVT</a>
Embodied Carbon (Cradle to Gate)	9.2 kg CO <sub>2</sub> eq./m <sup>2</sup>
Full Life Cycle Carbon	Certified Carbon Neutral Floors™
ReUse	Can be cleaned and reused in a non-critical location to extend its useful life.
Fully Recyclable	Can be recycled into carpet tile backing.
Material Composition	Free of Ortho Phthalates

**Technical Information**

Installation	<a href="#">See recommended LVT installation guidelines</a>
Maintenance	<a href="#">See recommended LVT maintenance guidelines</a>
Warranty	<a href="#">15 years LVT</a>

**Certifications**

EN ISO 10874 33 Heavy Commercial / 42 General Light Industrial

(ISO 4918 / EN425) Pass



(EN ISO 9239-1) Euroclass Bfl-s1 (EN 13501-1)



≥ 7



(ISO 23999) ≤ 0.25 %



(EN ISO 24344) Method A - Pass



≤0.2mm



(EN 660-2) Group T



(EN ISO 26987) Very Good



Yes



Yes



French A+



0.03



LVT



LVT