

A4 Multifunction Color

IM C401F IM C401SRF

RICOH
imagine. change.

✔ Printer ✔ Copier ✔ Scanner ✔ Fax



IM C401F
IM C401SRF



45-ppm

Powerful Features. Vibrant Results. Effortless Office Productivity.

Transform the way you work with the RICOH IM C401F and IM C401SRF. These A4 color multifunction printers (MFPs) deliver robust functionality, wide software compatibility, and an intuitive design that empower fast-paced offices. Whether printing, copying, scanning, or faxing, these models enable your team to share information quickly, securely, and with vibrant color.

Delivering professional-quality output, these devices are ideal for organizations seeking a balance between functionality, sustainability, and cost-efficiency, all in a space-saving design.

Key features:



Seamless Performance

Streamline your workflow with integrated print, copy, scan, and fax capabilities, enhanced by Ricoh's embedded software solutions for remote management, mobile connectivity, and document processing.



Superior Print Performance

Achieve fast print speeds of up to 45 ppm and crisp 1,200 x 1,200 dpi resolution, delivering vibrant colors and sharp, precise text for professional-grade documents.



Sustainable Design

Drive your sustainability efforts with ENERGY STAR-compliant MFPs, featuring 10% post-consumer recycled content, 42% less plastic packaging compared to previous models, and a sleep mode that cuts the power consumption of the Smart Operation Panel (SOP) by 45% when compared to previous generation models.



Advanced Security Features

Keep confidential information secured from unauthorized access with user authentication and the Erase All Memory function, which overwrites the drive at the end of life. Enable secured printing with advanced encryption and enhanced network security through features such as IEEE 802.11, 802.1x, and validate firmware and applications with Trusted Platform Module (TPM) 2.0.



User-Friendly Design

Boost productivity with the intuitive 10.1" SOP which simplifies navigation, while integrated stapling on the IM C401SRF makes finishing tasks effortless.



Simplifying Office Work, Empowering Productivity

The RICOH IM C401F and IM C401SRF are built to address the unique challenges of modern offices, providing reliable and efficient solutions for teams who need to quickly share and process information.

Whether it's scanning to digitize documents, printing high-quality color outputs, or securely managing sensitive data, these A4 color MFPs offer an efficient, streamlined solution.

With a focus on sustainability, data security, and intuitive operation, Ricoh ensures these devices support your goals while enhancing productivity and reducing operational complexity.

RICOH IM C401F/ IM C401SRF

MAIN SPECIFICATIONS

GENERAL	IM C401F	IM C401SRF
Warm-up time	Less than 24 seconds	
Recovery time	10 seconds	
First copy time (B/W / Full Color)	6.2 seconds / 7.4 seconds	6.7 seconds / 7.9 seconds
First print time (B/W / Full Color)	4.2 seconds / 5.4 seconds	4.8 seconds / 5.9 seconds
Continuous output speed	B/W: 45 ppm / 45 ppm (simplex / duplex) Full Color: 42 ppm / 38 ppm (simplex / duplex)	
Memory: standard	6GB (2GB mainframe and 4GB SOP)	
Storage	256GB SSD (Standard); 320GB HDD (Optional); 256GB FIPS-validated Enhanced Security SSD (Optional)	
Single-Pass Document Feeder (SPDF) capacity	50 sheets	
Weight	50 kg / 110.2 lbs	60 kg / 132.3 lbs
Dimensions: W x D x H	19.6" x 22.2" x 23.2"	24.2" x 22.2" x 27.8"
Power source	120V-127V, 60Hz	
COPIER		
Multiple copying	Up to 999 copies	
Resolution	Up to 600 x 600 dpi	
Zoom	From 25%-400% in 1% increments	
PRINTER		
CPU	Intel ApolloLake-I E3930 1.3GHz	
Printer language: standard	PCL5e/XL, PostScript®3™ Emulation, PDF Direct Print Emulation, MediaPrint: JPEG, TIFF	
Printer language: optional	Genuine Adobe® PostScript®3™, Adobe® PDF Direct Print	
Print resolution: maximum	Up to 1200 x 1200 dpi	
Network interface: standard	Mainframe: IEEE 802.11 a/b/g/n/ac - 2.4 GHz or 5 GHz can be selected; Ethernet 10BASE-T/100BASE-TX/1000BASE-T; USB Host Type A - USB Flash Memory, USB Host Type A - 1 port for optional keyboard or card reader	
Network interface: optional	Device Server Option (additional NIC port)	
Mobile printing capability	AirPrint, Mopria®, RICOH Smart Device Connector	
Fonts: standard	80 Roman fonts + 13 International fonts	
Fonts: PS3 optional	136 Roman fonts	
Windows® environments	Windows 10 (32-/64-bit), 11, Server 2016, Server 2019, Server 2022, Server 2025	
Mac OS environments	MacOS 10.11 and later (PostScript®3™ only)	
SAP® environments	SAP R/3, SAP S/4	
SCANNER		
Scanning speed: BW / Full Color	41 ipm (simplex) / 82 ipm (duplex)	
Resolution: maximum	Up to 600 dpi	
Compression method	B/W: TIFF (MH, MR, MMR, JBIG2), Color: JPEG	
File Formats	Single Page: TIFF, JPEG (greyscale or full colour), PDF, High Compression PDF, PDF/A, Encrypted PDF, Searchable PDF (OCR Option required) Multi Page: TIFF, PDF, High Compression PDF, PDF/A, Encrypted PDF, Searchable PDF (OCR Option required)	
Scan modes	Network: TCP/IP, Sending E-mail: SMTP, POP, IMAP4, Scan to Folder: SMB, FTP, Web Services on Devices for Scanning, Network TWAIN for Windows environments	
FAX		
Circuit	PSTN, PBX	
Transmission speed	3 seconds	
Modem speed: maximum	33.6 Kbps	
Resolution: standard	8 x 3.85 line/mm, 200 x 100 dpi (std.), 8 x 7.7 line/mm, 200 x 200 dpi (Detail, Photo)	
Compression method	MH, MR, MMR, JBIG	
Scanning speed (Simplex / Duplex; BW and Color, LT SEF)	40 / 80 ipm	
Memory	8 MB (320 pages)	

RICOH IM C401F/ IM C401SRF

MAIN SPECIFICATIONS

	IM C401F	IM C401SRF
PAPER HANDLING		
Supported paper size	Standard Paper Tray: Up to 8.5" x 11" / A4, Optional Paper Tray: Up to 8.5" x 14", Envelopes, Bypass: Up to 8.5" x 14", Postcard, Envelopes	
Paper input: standard	550-Sheet Tray, plus 100-Sheet Bypass	
Paper input: maximum	2,300 Sheets (standard 550-sheet tray, plus 100-sheet bypass tray and 3 optional 550-sheet paper feed units)	
Paper output: standard	100 sheets (face down), 250 sheets (internal finisher)	
Paper weights	Standard Trays: 60 - 163 g/m ² , Bypass Tray: 60 - 220 g/m ² , Duplex Unit: 60 - 163 g/m ²	
Paper types	Plain Paper, Recycled Paper, Color Paper, Letterhead, Preprinted Paper, Bond Paper, Cardstock, Label Paper, Waterproof Paper, Envelope, Coated Paper, Thick Paper 1-3	

SECURITY FEATURES		
Prevent unauthorized access to device	802.1x Wired Authentication, IEEE 802.11 Security (WEP, WPA, WPA2, WPA3), Quota Setting/Account Limit, User Authentication – Windows, LDAP via Kerberos, Basic, User Code Authentication, Wi-Fi Protected Setup (WPS) Support	
Prevent unauthorized access to network	IP Filtering – Access Control, IPsec Communication, Network Protocol On/Off, S/MIME, SMTP Over SSL/TLS, Secure Sockets Layer (SSL) Communication, Transport Layer Security (TLS 1.3), Network User Authentication	
Protection of confidential information	HDD/SSD Encryption, Trusted Platform Module (TPM) 2.0, Authentication Password Encryption, Unauthorized Copy Prevention – Print and Copy, Compulsory Security Stamp, Mask Type for Copying/Data Security for Copying, Encrypted Secure Print, Encrypted PDF Mode	
Protection of latent data	Erase All Memory function – to overwrite drive and NVRAM at machine end-of life Auto Erase Memory available when optional HDD is installed	

ENVIRONMENTAL FEATURES		
Power consumption: maximum	1,400 W or less	
Power consumption: ready / sleep	80 W or less / 0.50 W	
Typical Energy Consumption (TEC)	0.50 kWh	0.52 kWh
Energy Star®	Certified	
EPEAT®	Gold Rated*	

* EPEAT Gold rating is applicable only in the USA.

CONSUMABLES		
Toner (standard-yield black)*	Black Toner Cartridge: 19,300 prints	
Toner (standard-yield cyan/magenta/yellow)*	Color Toner Cartridges: 10,300 prints each	
Toner (high-yield black)*	Black Toner Cartridge: 19,800 prints	
Toner (high-yield cyan/magenta/yellow)*	Color Toner Cartridges: 13,700 prints each	
Staple set	N/A	5,000 staples
Staple refill	N/A	10,000 staples

* Declared toner yield in accordance with ISO/IEC 19798

PAPER SUPPLY OPTIONS		
550-Sheet Paper Feed Unit PB1230, Low Cabinet Type A12, Medium Cabinet Type A13, High Cabinet Type A14, Caster Table Type A11		

OTHER OPTIONS		
1 Bin Tray BN1050, PostScript®3™ Unit Type M59, OCR Unit Type M52, Device Server Option Type M52, HDD Option Type M52 320GB, FIPS-validated Enhanced Security SSD Option Type M52 256GB, Card Reader Cover Type M52, Optional Counter Interface Unit Type M12		

Terms and Conditions

- This device does not support PoE (Power over Ethernet) and should not be connected to a PoE hub. Connecting to a PoE hub could cause damage and void warranty coverage.
- Some options may not be available at the time of market release.
- Specifications are subject to change without notice.
- For maximum performance and yield, we recommend using genuine Ricoh parts and supplies.
- Some features may require additional options and/or charges.



RICOH
imagine. change.

Get in touch

(061) 303 666 | (01) 6111 025 | sales@m2.ie | www.m2.ie